



**Model 3840 Adapter, BNC (Male), Resistor Termination**



**Features:**

- Reliable termination at known resistance value  $\pm 1\%$
- Gold plated contacts for high conductance
- Tarnish resistant plating on body

**Materials:**

Body: Brass, Center Contact: Gold plated brass

Outer Contact: Tarnish Resistant gold plated Beryllium Copper.

Dielectric: Teflon

**Gasket/Seals: Silicone rubber**

Resistor: Deposited carbon film

Marking: "Pomona 3840"

Label: "TERM, \* $\Omega$  1/2W"

**Ratings:**

Frequency Range: DC to 500 MHz

Resistance Tolerance:  $\pm 1\%$

Power: 1/2W @ 70°C Max

**ORDERING INFORMATION:** Model 3840-\*

\*= Resistance Value 50, 75, 93, 100, 600

Ordering Example: 3840-50 = 50 Ohms

**Sales:**  
800-490-2361  
**Fax:**  
888-403-3360

**Technical Support:**  
800-241-2060  
or e-mail us at  
technicalsupport@pomonatest.com

*All dimensions are in inches. Tolerances (except noted): .xx =  $\pm .02$ " (.51 mm), .xxx =  $\pm .005$ " (.127 mm). All specifications are to the latest revisions. Specifications are subject to change without notice. Registered trademarks are the property of their respective companies.*