

151-00775

Article Number: 151-00775



Download drawing



Download spec sheet

Base Data

Local Order Number 151-00775
Type CCSFT6.5
Color Black (BK)

Features and Benefits Connector Clips are initially installed onto the appropriate mating connector found on a wire or cable harness assembly. The connector is then secured to the attachment surface using the connector clip mount. The attachment surface can be a hole, stud, or even another harness assembly depending on the connector clip mount being used.

Product Dimensions

Length L (Imperial) 0.91 "
Length L (Metric) 23.0 mm
Fixation Method Arrowhead (Small Mount)
Height H (Imperial) 0.48 "
Height H (Metric) 12.1 mm

Disc Diameter (Imperial) 0.63 "
Disc Diameter (Metric) 16.0 mm

Panel Thickness Max. (Imperial) 0.09 "

Panel Thickness Max. (Metric) 2.3 mm

Panel Thickness Min. (Imperial) 0.07 "

Panel Thickness Min. (Metric) 1.7 mm

Mounting Hole Diameter D (Imperial) 0.25-0.26 "

Mounting Hole Diameter D (Metric) 6.3 - 6.7 mm

Mounting Hole Diameter D Min. (Imperial) 0.24 "

Mounting Hole Diameter D Max. (Imperial) 0.26 "

Mounting Hole Diameter D Max. (Metric) 6.7 mm
6.3 mm

Mounting Hole Diameter D Min. (Metric)

Logistics and Packaging

Quantity Per bag
Package Quantity (Metric) 5000
Carton Quantity 5000 Pieces
Weight (Metric) 0.575 kg

Material and Specifications

Material Polyamide 6.6 high impact modified, heat stabilized, UV resistant (PA66HIRHS)

Material Shortcut PA66HIRHS

Flammability UL94 HB

Operating Temperature -40°F to +221°F (-40°C to +105°C)

ROHS Compliant Yes